

# EC-ESS24PS & EC-ESS24PSM

## 1/2" Square Drive 24 Piece Socket Sets

### Universal Joint

Flexible 180° twisting connector that allows for working at awkward angles or in hard-to-reach places. Fit directly onto the Ratchet and Extension Bars.

### Spark Plug Sockets

Designed specifically for working with spark plugs in vehicles, Spark Plug Sockets are deeper in length to accommodate the spark plug and have a rubber lining to ensure a secure fit, absorb vibration, and reduce any possibility of damaging the spark plug (especially the glad featured along the spark plug).

### 15 x Sockets (3/8" – 1 1/4")

The sockets featured in our Eclipse socket sets are six-point hex, meaning that the sockets have six angles/faces inside the bolt end

### Extension Bars

Affix to the Ratchet Handle or F-Bar to reach fasteners in confined or awkward spaces that are difficult to access



### 72T Ratchet Handle

Our Eclipse Ratchet Handles have 72 teeth on the drive gear, meaning that the handle must move just 5° to engage the next tooth

### Head Driver / F-Bar Handle

A Head Driver bar (also known as a Breaker, Power bar, or F Handle) is a non-ratcheting bar that is used to break loose very tight fasteners. The connector swings 180° and can be fixed in 3 different positions (left, right, or straight) for working at different angles. When fixed in the standard straight position, this handle also works like a screwdriver.

### 3 Way Adaptor

Slide this onto Extension Bars to create a T Handle ideal for creating greater torque when more force is needed on tough to move nuts and bolts.

**RRP \$149.98**

Barcode: (IMPERIAL) 5012095630029 & (METRIC) 5012095631132

## Logistical Information

Part No.	Single item no packaging				Single item with packaging				Inner pack (Carton)				Outer (Transit) pack where applicable					
	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Qty. per inner pack	Length (mm)	Width (mm)	Height (mm)	Weight (Kg)	Qty. per outer pack	Length (mm)	Width (mm)	Height (mm)	Weight (Kg)
EC-ESS24PS	N/A	N/A	N/A	4.48	330	245	80	4.48	5	340	260	440	25.5	N/A	N/A	N/A	N/A	N/A
EC-ESS24PSM	N/A	N/A	N/A	4.48	330	245	80	4.48	5	340	260	440	25.5	N/A	N/A	N/A	N/A	N/A

